

Catalyst 9200L-M Datasheet

Overview

The Catalyst 9200L-M meets the demands of enterprise applications by combining the simplicity of the Meraki dashboard with powerful switching hardware. It supports high-bandwidth applications and high-speed Wi-Fi access points with multigigabit ports and 80GB stacking. It offers either four fixed 1G/10G or two fixed 25G uplinks. The switch delivers resiliency through fast stack convergence. It uses Adaptive Policy with an over-the-wire tag to segment traffic into security groups, providing scalable security. Integrated with the Meraki dashboard, the Catalyst 9200L-M offers a simple yet powerful solution for demanding wired access applications.

Adaptive Policy provides simple & scalable security policies to segment traffic using Security Groups. Security Groups are created in the dashboard using natural language such as "IOT device" & "Guest." The security policy intent (e.g., Permit or Deny) is then simply provisioned between Security Groups which results in the segmentation of each group's traffic. By making security policy management intuitive and scalable relative to legacy IP-address based Access Control Lists, Adaptive Policy empowers operators to confidently secure their network traffic independent of future network changes.



A Catalyst 9200L switch can also be migrated to a Meraki-managed persona, where it would function as its Catalyst Meraki 9200L-M equivalent. For details on the migration process, refer to our [Getting started: Cisco Catalyst 9200 with Meraki Dashboard](#) guide.

Models

| Number of Ports | Model | Description |
|-----------------|-----------------|---|
| 24 Ports | C9200L-24T-4G-M | 24-port 1 GbE Data with 4x 1G fixed uplinks, PWR-C5-125WAC |
| | C9200L-24P-4G-M | 24-port 1GbE PoE+ with 4x 1G fixed uplinks, PWR-C5-600WAC |
| | C9200L-24T-4X-M | 24-port 1 GbE Data with 4x 1G/10G fixed uplinks, PWR-C5-125WAC |
| | C9200L-24P-4X-M | 24-port 1GbE PoE+ with 4x 1G/10G fixed uplinks, PWR-C5-600WAC |

| Number of Ports | Model | Description |
|-----------------|-------------------|---|
| | C9200L-24PXG-4X-M | 24-port PoE+, 8 mGig(10G/5G/2.5G/1G/100M) with 4x 1G/10G fixed uplinks, PWR-C5-600WAC |
| | C9200L-24PXG-2Y-M | 24-port PoE+, 8 mGig(10G/5G/2.5G/1G/100M) with 2x 1G/10G/25G fixed uplinks, PWR-C5-600WAC |
| 48 Ports | C9200L-48T-4G-M | 48-port 1 GbE Data with 4x 1G fixed uplinks, PWR-C5-125WAC |
| | C9200L-48P-4G-M | 48-port 1GbE PoE+ with 4x 1G fixed uplinks, PWR-C5-1KWAC |
| | C9200L-48PL-4G-M | 48-port 1GbE partial PoE+ with 4x 1G fixed uplinks, PWR-C5-600WAC |
| | C9200L-48T-4X-M | 48-port 1 GbE Data with 4x 1G/10G fixed uplinks, PWR-C5-125WAC |
| | C9200L-48P-4X-M | 48-port 1GbE PoE+ with 4x 1G/10G fixed uplinks, PWR-C5-1KWAC |
| | C9200L-48PL-4X-M | 48-port 1GbE partial PoE+ with 4x 1G/10G fixed uplinks, PWR-C5-600WAC |
| | C9200L-48PXG-4X-M | 48-port PoE+, 12 mGig(10G/5G/2.5G/1G/100M) with 4x 1G/10G fixed uplinks, PWR-C5-1KWAC |
| | C9200L-48PXG-2Y-M | 48-port PoE+, 8 mGig(10G/5G/2.5G/1G/100M) with 2x 1G/10G/25G fixed uplinks, PWR-C5-1KWAC |

Features

| Category | Features |
|------------|---|
| Highlights | <ul style="list-style-type: none"> Layer-3 |

| Category | Features |
|--|--|
| | <ul style="list-style-type: none"> • Four SFP+(10G/1G) fixed uplinks on 4X models • Two SFP28(25G/10G/1G) fixed uplinks on 2Y models • mGig support on XG models • 80G Dual Dedicated Hardware Stacking Ports • PoE+ (30W per port) & IEEE 802.3at • Redundant hotswappable power supplies |
| Management | <ul style="list-style-type: none"> • Managed via Cisco Meraki Dashboard • Zero-touch remote provisioning (no staging needed) • Basic configuration capability via local management page • Detailed historical per-port and per-client usage statistics • Operating System, device, and hostname fingerprinting • Automatic firmware upgrades with scheduling control • SNMP and SYSLOG support for integration with other network management solutions |
| Remote Diagnostics | <ul style="list-style-type: none"> • Email, SMS and Mobile push notification alerts • Ping, traceroute, cable testing, and link failure detection with alerting • Remote packet capture • Dynamic and interactive network discovery and topology • Combined event and configuration change logs with instant search |
| Stacking** | <ul style="list-style-type: none"> • Optional stacking kit allowing 8 switches in a stack with 80Gbps of stacking bandwidth • Virtual stacking supports thousands of switch ports in a single logical stack for unified management, monitoring, and configuration • Faster convergence |
| Ethernet Switching Capabilities | <ul style="list-style-type: none"> • 802.1p Quality of Service, 8 queues (w/ 6 configurable for DSCP-to-CoS mapping) • 802.1Q VLAN and trunking support for up to 4,094 VLANs (1000 active VLANs with STP enabled) • Single Instance of 802.1s Multiple Spanning Tree Protocol (interoperable with RSTP, STP, PVST, RPVST) • STP Enhancements: BPDU guard, Root guard, Loop guard, UDLD • Broadcast storm control • 802.1ab Link Layer Discovery Protocol (LLDP) and Cisco Discovery Protocol (CDP) • 802.3ad Link aggregation with up to 8 ports per aggregate, multi-chassis aggregates supported on stacked switches • Port mirroring • IGMP snooping for multicast filtering • MAC Forwarding Entries: 16K |
| Layer 3 | <ul style="list-style-type: none"> • Static routing, OSPFv2 • Multicast routing (ASM: PIM-SM) • Warm Spare (VRRP) * • DHCP Server, DHCP Relay |

| Category | Features |
|----------|---|
| Security | <ul style="list-style-type: none"> • Integrated multi-factor authentication for Dashboard management • Role-based access control (RBAC) with granular device and configuration control • Corporate wide password policy enforcement • IEEE 802.1X RADIUS and MAB, hybrid authentication and RADIUS server testing • Single-Host/Multi-Domain/Multi-Host/Multi Authentication • Port security: Sticky MAC, MAC Allow listing * • DHCP snooping, detection and blocking, Dynamic ARP Inspection • IPv4 and IPv6 ACLs • Secure Connect * • Adaptive Policy |



* Available in a future software release

**Stacking Limit for C9200L(-M): C9200L series models running Cloud Management with IOS XE 17.15+ support stacking configurations of up to 5 members. Please ensure your stacks for these models adhere to this limit. Exceeding 5 members may lead to unexpected behavior. This will be resolved in a future release.

Catalyst 9200L-M Licensing

The Catalyst 9200L-M license applies to all C9200L hardware platforms. Catalyst 9200L-M license structure includes two feature tiers: Enterprise and Advanced. As with all Meraki managed switches, every Catalyst 9200L-M license is available in 1, 3, and 5 year terms.

| Catalyst 9200L-M License Structure | 24-Port | 48-port |
|------------------------------------|----------------|----------------|
| Advanced Features | LIC-C9200L-24A | LIC-C9200L-48A |
| Enterprise Features | LIC-C9200L-24E | LIC-C9200L-48E |

The features available with advanced licensing are:

- [Adaptive policy](#)
- [Netflow v10 \(IPFIX\) and Encrypted Traffic Analytics](#)



In the Co-term licensing model (most existing Organizations), an Organization must either have all Catalyst 9200L-M Enterprise or all Catalyst 9200L-M Advanced licenses - they cannot be mixed. In the Per-device licensing model, a mix of Enterprise and Advanced can be added to a single Organization, but certain features may require all devices in a Network to have Advanced licenses, e.g. Adaptive Policy.



[MS390s](#) and or Catalyst 9300L/X-M existing in the same co-term Organization will require the *same* license edition (either Enterprise or Advanced) as the Catalyst 9200L-M. License types cannot be mixed and will result in an incompatible license error.

For more information on licensing, refer to [Meraki Licensing Models article](#).

[Subscription licensing](#) is also available for the Catalyst 9200L-M switches

Technical Breakdown

Interfaces Specifications

| Model | Interfaces | Fixed Uplinks (SFP+/SFP28) | 80G Hardware Stack Ports | Dedicated Management Interface | PoE Capabilities |
|-------------------|---|-------------------------------|-----------------------------|--------------------------------------|---------------------|
| C9200L-24T-4G-M | 24 1G ports data | 4x 1G SFP | 2 | 1 | n/a |
| C9200L-24P-4G-M | 24 1G ports full PoE+ | 4x 1G SFP | 2 | 1 | 30W PoE+ |
| C9200L-24T-4X-M | 24 1G ports data | 4x 10G/1G SFP+ | 2 | 1 | n/a |
| C9200L-24P-4X-M | 24 1G ports full PoE+ | 4x 10G/1G SFP+ | 2 | 1 | 30W PoE+ |
| C9200L-24PXG-4X-M | 24 ports full PoE+ (8 mGig ports up to 10G, 16 ports up to 1G) | 4x 10G/1G SFP+ | 2 | 1 | 30W PoE+ |
| C9200L-24PXG-2Y-M | 24 ports full PoE+ (8 mGig ports up to 10G, 16 ports up to 1G) | 2x 25G/10G/1G SFP28 | 2 | 1 | 30W PoE+ |
| C9200L-48T-4G-M | 48 1G ports data | 48 ports data | 2 | 1 | n/a |
| C9200L-48P-4G-M | 48 1G ports full POE+ | 4x 1G SFP | 2 | 1 | 30W PoE+ |
| C9200L-48PL-4G-M | 48 1G ports partial PoE+ | 4x 1G SFP | 2 | 1 | 30W PoE+ |
| C9200L-48T-4X-M | 48 1G ports data | 4x 10G/1G SFP+ | 2 | 1 | n/a |
| C9200L-48P-4X-M | 48 1G ports full PoE+ | 4x10G/1G SFP+ | 2 | 1 | 30W PoE+ |
| C9200L-48PL-4X-M | 48 1G ports partial PoE+ | 4x 10G/1G SFP+ | 2 | 1 | 30W PoE+ |
| C9200L-48PXG-4X-M | 48 ports full POE+ (12 mGig ports up to 10G, 36 ports up to 1G) | 4x 10G/1G SFP+ | 2 | 1 | 30W PoE+ |

| Model | Interfaces | Fixed Uplinks (SFP+/SFP28) | 80G Hardware Stack Ports | Dedicated Management Interface | PoE Capabilities |
|--------------------------|--|-------------------------------|-----------------------------|--------------------------------------|---------------------|
| C9200L-48PXG-2Y-M | 48 ports full POE+ (8 mGig ports up to 10G, 40 ports up to 1G) | 2x 25G/10G/1G SFP28 | 2 | 1 | 30W PoE+ |



For supported SFP modules refer the [SFP Datasheet](#).



Cabling Best Practices for Multi-Gigabit operations: While Category-5e cables can support multigigabit data rates up to 2.5/5/10 Gbps, external factors such as noise, alien crosstalk coupled with longer cable/cable bundle lengths can impede reliable link operation. Noise can originate from cable bundling, RFI, cable movement, lightning, power surges and other transient event. It is recommended to use Category-6a cabling for reliable multigigabit operations as it mitigates alien crosstalk by design.

Physical Specifications

| Model | Dimensions (h x w x d) W/ Default Power Supply | Weight w/ Default Power Supply | Mount Type | Hot Swap Fans | Operating Temperature | Humidity |
|--------------------------|---|-----------------------------------|---------------|---------------|-----------------------|----------|
| C9200L-24T-4G-M | 1.73 x 17.5 x 12.9" (4.4 x 44.5 x 32.9cm) | 9.59 lb (4.35 kg) | 1U Rack Mount | No, 2x | -5°C to 45°C | 5 to 90% |
| C9200L-24P-4G-M | 1.73 x 17.5 x 12.9" (4.4 x 44.5 x 32.9cm) | 10.38 lb (4.71 kg) | 1U Rack Mount | No, 2x | -5°C to 45°C | 5 to 90% |
| C9200L-24T-4X-M | 1.73 x 17.5 x 12.9" (4.4 x 44.5 x 32.9cm) | 9.59 lb (4.35 kg) | 1U Rack Mount | No, 2x | -5°C to 45°C | 5 to 90% |
| C9200L-24P-4X-M | 1.73 x 17.5 x 12.9" (4.4 x 44.5 x 32.9cm) | 10.38 lb (4.71 kg) | 1U Rack Mount | No, 2x | -5°C to 45°C | 5 to 90% |
| C9200L-24PXG-4X-M | 1.73 x 17.5 x 15.4" (4.4 x 44.5 x 39.1cm) | 12 lb (5.44 kg) | 1U Rack Mount | No, 2x | -5°C to 45°C | 5 to 90% |
| C9200L-24PXG-2Y-M | 1.73 x 17.5 x 15.4" | 12 lb (5.44 kg) | 1U Rack Mount | No, 2x | -5°C to 45°C | 5 to 90% |

| Model | Dimensions (h x w x d) W/ Default Power Supply | Weight w/ Default Power Supply | Mount Type | Hot Swap Fans | Operating Temperature | Humidity |
|--------------------------|---|-----------------------------------|---------------|---------------|-----------------------|-----------|
| | (4.4 x 44.5 x 39.1cm) | | | | | |
| C9200L-48T-4G-M | 1.73 x 17.5 x 12.9" (4.4 x 44.5 x 32.9cm) | 9.97 lb (4.53 kg) | 1U Rack Mount | No, 2x | -5°C to 45°C | 5 to 90% |
| C9200L-48P-4G-M | 1.73 x 17.5 x 12.9" (4.4 x 44.5 x 32.9cm) | 10.58 lb (4.80 kg) | 1U Rack Mount | No, 2x | -5°C to 45°C | 5% to 90% |
| C9200L-48PL-4G-M | 1.73 x 17.5 x 12.9" (4.4 x 44.5 x 32.9cm) | 10.58 lb (4.80 kg) | 1U Rack Mount | No, 2x | -5°C to 45°C | 5% to 90% |
| C9200L-48T-4X-M | 1.73 x 17.5 x 12.9" (4.4 x 44.5 x 32.9cm) | 9.97 lb (4.53 kg) | 1U Rack Mount | No, 2x | -5°C to 45°C | 5% to 90% |
| C9200L-48P-4X-M | 1.73 x 17.5 x 12.9" (4.4 x 44.5 x 32.9cm) | 10.58 lb (4.80 kg) | 1U Rack Mount | No, 2x | -5°C to 45°C | 5% to 90% |
| C9200L-48PL-4X-M | 1.73 x 17.5 x 12.9" (4.4 x 44.5 x 32.9cm) | 10.58 lb (4.80 kg) | 1U Rack Mount | No, 2x | -5°C to 45°C | 5% to 90% |
| C9200L-48PXG-4X-M | 1.73 x 17.5 x 15.4" (4.4 x 44.5 x 39.1cm) | 12.6 lb (5.71 kg) | 1U Rack Mount | No, 2x | -5°C to 45°C | 5% to 90% |
| C9200L-48PXG-2Y-M | 1.73 x 17.5 x 15.4" (4.4 x 44.5 x 39.1cm) | 12.6 lb (5.71 kg) | 1U Rack Mount | No, 2x | -5°C to 45°C | 5% to 90% |

Performance

| Model | Switching Capacity | Stacking Bandwidth | Forwarding rate Single / Stack |
|------------------------|--------------------|--------------------|-----------------------------------|
| C9200L-24T-4G-M | 56 Gbps | 136 Gbps | 41.67 Mpps / 101 Mpps |

| Model | Switching Capacity | Stacking Bandwidth | Forwarding rate Single / Stack |
|-------------------|--------------------|--------------------|-----------------------------------|
| C9200L-24P-4G-M | 56 Gbps | 136 Gbps | 41.67 Mpps / 101 Mpps |
| C9200L-24T-4X-M | 128 Gbps | 208 Gbps | 95.23 Mpps / 155 Mpps |
| C9200L-24P-4X-M | 128 Gbps | 208 Gbps | 95.23 Mpps / 155 Mpps |
| C9200L-24PXG-4X-M | 272 Gbps | 352 Gbps | 214.28 Mpps / 262 Mpps |
| C9200L-24PXG-2Y-M | 292 Gbps | 372 Gbps | 229.16 Mpps / 277 Mpps |
| C9200L-48T-4G-M | 104 Gbps | 184 Gbps | 77.38 Mpps / 137 Mpps |
| C9200L-48P-4G-M | 104 Gbps | 184 Gbps | 77.38 Mpps / 137 Mpps |
| C9200L-48PL-4G-M | 104 Gbps | 184 Gbps | 77.38 Mpps / 137 Mpps |
| C9200L-48T-4X-M | 176 Gbps | 256 Gbps | 130.95 Mpps / 190 Mpps |
| C9200L-48P-4X-M | 176 Gbps | 256 Gbps | 130.95 Mpps / 190 Mpps |
| C9200L-48PL-4X-M | 176 Gbps | 256 Gbps | 130.95 Mpps / 190 Mpps |
| C9200L-48PXG-4X-M | 392 Gbps | 472 Gbps | 291.66 Mpps / 351 Mpps |
| C9200L-48PXG-2Y-M | 340 Gbps | 420 Gbps | 252.97 Mpps / 313 Mpps |

Power Supply and Specifications

| Model | Default Power Supply | Hot Swap Power Supply | Available PoE W/ Primary PS | PoE W/ Secondary PS** | Power Load (idle/max) |
|-------------------|----------------------|-----------------------|-----------------------------|-----------------------|-----------------------|
| C9200L-24T-4G-M | PWR-C5-125WAC | Yes, Dual | n/a | n/a | 27.39 / 36.23 W |
| C9200L-24P-4G-M | PWR-C5-600WAC | Yes, Dual | 370W | 740W | 39.59 / 466.34 W |
| C9200L-24T-4X-M | PWR-C5-125WAC | Yes, Dual | n/a | n/a | 27.82 / 38.6 W |
| C9200L-24P-4X-M | PWR-C5-600WAC | Yes, Dual | 370W | 740W | 39.48 / 434.06 W |
| C9200L-24PXG-4X-M | PWR-C5-600WAC | Yes, Dual | 370W | 740W | 64.54 / 472.39 W |
| C9200L-24PXG-2Y-M | PWR-C5-600WAC | Yes, Dual | 370W | 740W | 65.58 / 489.62 W |
| C9200L-48T-4G-M | PWR-C5-125WAC | Yes, Dual | n/a | n/a | 33.85 / 47.33 W |

| Model | Default Power Supply | Hot Swap Power Supply | Available PoE W/ Primary PS | PoE W/ Secondary PS** | Power Load (idle/max) |
|-------------------|----------------------|-----------------------|-----------------------------|-----------------------|-----------------------|
| C9200L-48P-4G-M | PWR-C5-1KWAC | Yes, Dual | 740W | 1440W | 45.82 / 933.03 W |
| C9200L-48PL-4G-M | PWR-C5-600WAC | Yes, Dual | 370W | 740W | 39.59 / 466.34 W |
| C9200L-48T-4X-M | PWR-C5-125WAC | Yes, Dual | n/a | n/a | 36.08 / 53.60 W |
| C9200L-48P-4X-M | PWR-C5-1KWAC | Yes, Dual | 740W | 1440W | 50.31 / 872.6 W |
| C9200L-48PL-4X-M | PWR-C5-600WAC | Yes, Dual | 370W | 740W | 40.17 / 445.35 |
| C9200L-48PXG-4X-M | PWR-C5-1KWAC | Yes, Dual | 740W | 1440W | 72.14 / 930.11 W |
| C9200L-48PXG-2Y-M | PWR-C5-1KWAC | Yes, Dual | 740W | 1440W | 71.45 / 934.08 W |



* Limited by port number and port rating (e.g. 24 PoE+ 30W ports = 720W)

** The PoE values are provided considering the secondary PS to be the default power supply of the respective model.

C6 variant is not supported in C9200L. Please refer to [Unsupported Power Supplies on Catalyst 9200 and 9200L switches](#)

Package contents

In addition to the MS switch, each shipment includes the following.

- 1 x default power supply unit for the switch model (please refer to the [Power Supply and Specifications](#) section)
- Rack mount brackets
- 2 x Pre-installed fans.
- STACKING NOTE: The C9200L does NOT include stacking ports by default. Please order the C9200L-STAK-KIT-M with every C9200L switch that you plan to deploy in a stack. That kit includes two stacking ports and a 50cm stacking cable.

Optional Accessories

| Accessory | Description |
|-----------------|-----------------------|
| PWR-C5-125WAC-M | 125W AC Power Supply |
| PWR-C5-600WAC-M | 600W AC Power Supply |
| PWR-C5-1KWAC-M | 1000W AC Power Supply |

| Accessory | Description |
|---------------------------|---|
| C9200L-STACK-KIT-M | Stack Kit for 9200L. Includes two adapters and one 50cm stack cable |
| STACK-T4-50CM-M | 50 cm Stacking Cable Spare |
| STACK-T4-1M-M | 1m Stacking Cable Spare |
| STACK-T4-3M-M | 3M Stacking Cable Spare |

SFP Modules

The following SFP/Fiber transceivers are supported. For detailed SFP specifications, refer to the [Meraki SFP datasheet](#). For information about Cisco Optics compatibility, please click [here](#)

Transceiver Model Standard

1 Gbps

| | |
|-----------------|--|
| MA-SFP-1GB-SX | 1000BASE-SX over OM1/2/3/4 up to distances of 1KM |
| MA-SFP-1GB-LX10 | 1000BASE-LX10 over OS1/OS2 up to distances of 10KM |

10 Gbps

| | |
|----------------|--|
| MA-SFP-10GB-SR | 10GBASE-SR over OM1/2/3/4 up to distances of 400 M |
| MA-SFP-10GB-LR | 10GBASE-LR over OS1/2 up to distances of 10 KM |
| MA-SFP-10GB-ER | 10GBASE-ER over OS1/2 up to distances of 40 KM |
| MA-SFP-10GB-ZR | 10GBASE-ZR over OS1/2 up to distances of 80 KM |

Direct Attach

| | |
|--------------|--------------------------|
| MA-CBL-TA-1M | 10GSFP+Cu Passive Twinax |
| MA-CBL-TA-3M | |

Regulations and Compliance

Electromagnetic Compatibility

FCC Part 15 (CFR 47) Class A ICES-003 Class A EN 55032 Class A CISPR 32 Class A AS/NZS 3548 Class A BSMI Class A VCCI Class A CISPR 35 EN 55035, EN300 386* , EN 61000-3-2, EN 61000-3-3

Certifications

| | |
|----------------------|---|
| Safety | UL 60950-1/62368-1, CAN/CSA-C22.2 No. 60950-1/62368-1, EN 60950-1/62368-1, IEC 60950-1/62368-1, CCC, CE Marking |
| Environmental | Reduction of Hazardous Substances (ROHS) 5 |
| Warranty | Full lifetime hardware warranty with next-day advanced replacement included |

MTBF Rating

| Model | MTBF |
|-------------------|---------|
| C9200L-24T-4G-M | 531,030 |
| C9200L-24P-4G-M | 392,210 |
| C9200L-24T-4X-M | 525,990 |
| C9200L-24P-4X-M | 390,310 |
| C9200L-24PXG-4X-M | 379,410 |
| C9200L-24PXG-2Y-M | 374,730 |
| C9200L-48T-4G-M | 508,700 |
| C9200L-48P-4G-M | 347,760 |
| C9200L-48PL-4G-M | 347,760 |
| C9200L-48T-4X-M | 503,400 |
| C9200L-48P-4X-M | 346,270 |
| C9200L-48PL-4X-M | 346,270 |
| C9200L-48PXG-4X-M | 379,410 |
| C9200L-48PXG-2Y-M | 337,360 |

Installation Guide

For instructions on how to install and configure the C9200L series switch refer the [C9200L Series Installation Guide](#)